

ZONITH BLUETOOTH PANIC BUTTON, MODEL BT-PANIC-BUTTON

ENCLOSURE

Size: W:67 x H:90 x D:19,6 mm
IP Code: IP40
Weight: 89 gram (with batteries)
Color: White

AMBIENT TEMPERATURES

Operating: Max: +50 °C, Min: -10 °C
Storage: Max: +50 °C, Min: 0 °C

BLUETOOTH

BT 4.0 and BT 4.1 stack BLE

TRANSCEIVER

TX Power: -20 to +4dBm
Frequency: 2.4 – 2.485 GHz
Adaptive Frequency Hopping (AFH)
Sensitivity: -93dBm Bluetooth LE

MOUNTING

2 pcs screws.
Head diameter: 7 mm
Screw diameter: 3,7 mm
Distance between mounting holes: 44 mm

BATTERY

3 pcs. CR2477
(non-chargerable, replaceable)
Estimated battery life: 3 - 5 years
Estimate based on room temperature [20°C].
Colder environments will affect life time.

RANGE

Max distance to ZONITH BT Receiver:
15 - 20 meters (49 – 65 feet)
in open space.

APPROVALS AND DECLARATION OF CONFORMITY

FCC/CE/IC

COUNTRY OR ORIGIN

Denmark



PANIC BUTTON

Disclaimer

Zonith A/S makes no warranties that all functionality is supported neither by the local network nor by the selected Bluetooth devices used by the system. Specifications are subject to change without notice. All product or service names are the property of their respective owners.

COPYRIGHT AND TRADEMARK INFO

© 2019 ZONITH A/S. ZONITH, The ZONITH logo and "ZONITH Bluetooth Panic Button" is a trademark of ZONITH A/S. All rights reserved.